

SOLVING YOUR CHALLENGES

SATEL is a leading expert and innovator in independent radio networking technology. We develop high-quality private radio technology solutions that enable secure, mission-critical connections.

Our solutions are used in wide range of industrial applications. We are known for our high quality and expertise. All SATEL radio modems are designed and manufactured in Finland.

Reliable connections, protected business

SATEL radio technology is easy and fast to implement and use, and has low life cycle costs.

The solutions we offer are also expandable, customizable, flexible and secure. You get added value from our services. We offer network design and technical support, and we have a wide distributor network at your service.



Expertise
High quality
Easy implementation
Independence

Operational security
Low life cycle costs
Service and support
Global distribution network





ENVIRONMENTAL MONITORING

Wireless radio technology is one key aspect in Environmental Monitoring. It brings safety, operability and control. With SATEL's solutions you can monitor weather conditions and get information for example in flood, fire or drought situation. They provide real-time information of environmental conditions without additional costs and with a minimum supervision.



OEM

SATEL have produced a range of OEM radio modules for system manufacturers to integrate into customer solutions. They are secure, customizable and flexible in mounting options. SATEL's solutions are widely compatible and also support other manufacturers' radio protocols.



UTILITIES

Utility systems require a highly reliable monitoring and controlling network. Malfunctions should be pinpointed quickly and even restored remotely. SATEL offers comprehensive solutions that are easy to implement and expand. SATEL radio technology is currently being used e.g. in power distribution, advanced metering infrastructure, windmills, waterworks, sewer networks, district heating and gas pipelines.



ITS

Intelligent Transport Systems are improving travel experience everywhere, and operational communication is a major factor in this. Private radio data network ensures the functionality of these applications. SATEL's radio technology is used in in public transport e.g. in traffic light and traffic sign control, real-time passenger information systems and automatic vehicle location.



MACHINE CONTROL

Machine control is used to accurately position machinery based on GNSS systems and 3D design models. Several machine control systems use the Real-Time Kinematic (RTK) to improve positioning accuracy for streamlining the different construction site workflows.

SATEL's radio technology is used worldwide in machine control. Our technology is perfect for mission-critical operations. It is a safe way to ensure availability even in areas with limited coverage or no coverage at all.

THE HEART OF THE SATEL XPRS SOLUTION

SATEL XPRS IP radio router is an excellent choice for data transfer for mission-critical applications requiring long range and the benefits of the privately owned networks.

The IP radio router provides high availability connections with device and routing protection. The SATEL XPRS solution utilizes the interoperability of the radio routers with other communications technologies, as well as technology switchovers.






SATEL XPRS IP radio router is suitable for both serial and IP data networking in UHF and VHF frequencies. It provides a reliable data connectivity for applications that require stability, high availability and long range. It supports low latency networking and has easy remote management with intuitive user interface.

The product consists of two separate modules, a radio unit and central unit. The radio unit alone can be used as a serial data radio router and as a repeater in packet routing networks. When central unit is added to the radio unit, full TCP/IP functionality is obtained. Advanced features, such as adaptive modulation and radio parameters, cyber security features, monitoring and management, protocol routing and conversion functionality provide a complete digital solution that takes into account all data transfer scenarios.








Radio and central unit w/o display YF0110 / YF0210 / YF0510




Radio and central unit w display YF0120 / YF0220 / YF0520

	XT 5R (FSK)		XT 5RC (FSK)		XT 5R (QAM)		XT 5RC (QAM)	
Model / Type identification	SATELLAR RU / TA-26		SATELLAR RU / TA-26		SATELLAR RU-Q / TA-26		SATELLAR RU-Q / TA-26	
SATEL order code with display	YF0	100	YF0110 YF0120		YF0200 UHF / YF0500 VHF		YF0210 UHF / YF0510 VHF YF0220 UHF / YF0520 VHF	
Frequency MHz		360-	-405		135-175			
		400-	-445		360-405			
		440-	-485			40	0-445	
Modulations		4, 8, 1	6 FSK		2,4	I, 8, 16, 32, 64 QA	M (2QAM only f	or UHF)
Tuning range				40 /	45 MHz			
Channel width		12.5 kHz / 25	kHz / 150 kHz			12.5 kH	Hz / 25 kHz	
Data speed radio (max.)	19.2 kbps @ 12.5 kHz (16FSK) 38.4 kbs @ 25 kHz (16FSK) 230 kbps @150 kHz (16FSK)				60.5 kbps @ 12.5 kHz (64QAM) 121 kbps @ 25 kHz (64QAM) Max. coded			
RX sensitivity (BER 10E-6)	Air speed	Channel width	Modulation	Sensitivity (10E-6)	Air speed	Channel width	Modulation	Sensitivity (10E-6) UHF / VHF
	230.4 kbps	150 kHz	16FSK	-82 dBm	121 kbps	25 kHz	64QAM	-98 / -98 dBm
	38.4 kbps	25 kHz	16FSK	-94 dBm	60.5 kbps	12.5 kHz	64QAM	-100 / -99 dBm
	19.2 kbps	12.5 kHz	16FSK	-97 dBm	80.6 kbps	25 kHz	16QAM	-105 / -104 dBm
	115.2 kbps	150 kHz	4FSK	-97 dBm	40.3 kbps	12.5 kHz	16QAM	-106 / -106 dBm
	19.2 kbps	25 kHz	4FSK	-108 dBm	40.3 kbps	25 kHz	4QAM	-111 / -110 dBm
	9.6 kbps	12.5 kHz	4FSK	-114 dBm	20.2 kbps	12.5 kHz	4QAM	-113 / 113 dBm
TX power (nominal)	37 dBm (5 W)				37 dBm (5 W) mean: average 30 dBm (1 W), max 32 dBm (1.5 W) PEP: average 37 dBm (5 W), max 38 dBm (6.6 W)			
Interface	RS-232, -	122 / -485	RS-232, -422 / -485, USB, Ethernet		RS-232, -422 / -485		RS-232, -422 / -485, USB, Ethernet	
Operating voltage	+ 10.6 Vo				lc +30 Vdc			
Power consumption without display TX / RX with display TX / RX	22.8 W / 2.8 W		24.4 W / 4.2 W 24.8 W / 4.8 W		UHF 14.4 W / 3.8 W	VHF 16 W / 4.4 W	UHF 15.8 W / 5.2 W 16.4 W / 5.8 W	VHF 17.4 W / 5.8 W 18 W / 6.4 W

Long range	VL	AN	Unicast Broadcast	ridge 10de	N	IETCO	<u>'</u>	Redundant routing	SNM monito	-	1	dio data up to 0 kbps	
Protoco conversio			:-104/101, DN odbus TCP/R	Firew	all	0.1-5 \ TX-pow		Interoper- ability	Serial over IP	Cyb	1	UHF / VHF	










FEATURES		
Included	Order separately	Explanation
Routed mode Bridge broadcast mode Transparent mode for serial	Proxy ARP	IP routing to remote networks in the same LAN or IP address range
Firewall (iptables, ebtables)	NMS to Modbus	Diagnostics with Modbus protocol
SSH access	Application routing	DNP3 IP to serial, Modbus TCP to Modbus RTU, Serial IP, UDP/TCP Proxy, Sinaut S7, custom protocol etc.
VLAN support	IEC104/IEC101 conversion	Protocol master is using IEC 60870-5-104 RTUs operate on IEC 60870-5-101
Encryption AES128, AES256	Redundant routing	IP routing table enhancement: Automatic route selection VRRP and other related features for high availability
Link specific modulation (Each remote can operate on separate modulation)	Adaptive modulation	Radio interface automatically adapts to SNR level
SNMPv1, 2, 3	Upgrade 16QAM to 32QAM	To achieve higher radio bit rate, up to 101 kbps
USB diagnostics port	Upgrade 16QAM to 64QAM	To achieve higher radio bit rate, up to 121 kbps
	Upgrade 32QAM to 64QAM	To achieve higher radio bit rate, up to 121 kbps

0.1-5 W TX-power	Inter- operatibility	Unicast Broadcast	VLAN	Bridge mode	SNMP moritoring	Firewall
Spectral efficient	Long range	Cyber- secure	NETCO	Remote configuration	Cost- effective	UHF / VHF



BENEFIT FROM THE USE OF **MULTIPLE TECHNOLOGIES** The SATEL XPRS solution takes your missioncritical communications to the next level. Varying system requirements such as different investment profiles and increasing redundancy and performance are met by the SATEL XPRS solution with wireless cellular routers.

Co-operation of adjacent technologies adds even more reliability, predictability and security to your mission-critical connectivity.



SATEL-GW120

SATEL order code SATEL-GW100 without WiFi SATEL-GW120 with WiFi	YG0100 YG0120
Cellular technologies	LTE, HSPA+, HSPA, UMTS, EDGE, GPRS, GSM
Interfaces	Dual SIM, 2.4 GHz WiFi, Dual Ethernet ports
Cyber security	For example IPsec and OpenVPN

The small and robust 2G/3G/LTE router with WiFi option is perfect for M2M applications like remote monitoring and control. It offers a new entry point for 2G/3G/LTE data applications and supports the following radio access technologies: LTE, HSPA+, HSPA, UMTS, EDGE, GPRS and GSM.

- Dual SIM
- · 2.4GHz WiFi
- Dual Ethernet
- Extended list of routing protocols
- Security features
- · GPS receiver
- SMS management
- Active power conditioning
- · Centralised management and monitoring

In case WiFi is not needed, a good choice is SATEL-GW100. It has all the same functions than SATEL-GW120 except WiFi.

SATEL-GW600	
SATEL order code	YG0600
Cellular technologies	LTE, HSPA+, HSPA, UMTS, EDGE, GPRS, GSM
Interfaces	Dual SIM, Quad Ethernet ports, RS- 232 and RS-485 serial ports, Digital inputs for event detection
Cyber security	For example IPsec and OpenVPN
Special features	Protocol conversions, Relay contact options, Interface connectivity monitoring

The versatile 2G/3G/LTE wireless router is suitable for a variety of industrial deployments. The compact structure makes it excellent for M2M applications like SCADA, telemetry and intelligent traffic systems. The router supports the following radio access technologies: LTE, HSPA+, HSPA, UMTS, EDGE, GPRS and GSM.

- Dual SIM
- Quad Ethernet ports
- SMS commands
- RS-232 and RS-485 serial ports
- Digital inputs for event detection
- Relay contact options
- Extended list of routing protocols
- Security features
- Protocol conversions
- · Centralised management and monitoring


FRONT PANEL



REAR PANEL







* NETWORK **MANAGEMENT SYSTEM**

SATEL NMS software can be used to set up a new radio modem network or modify an existing one. It is also an excellent tool for monitoring the condition of the radio network, and by setting different alarm levels it enables immediate reactions.

- Graphical tool for designing a radio network
- Enhanced reliability through advance indication of anticipated faults and failures
- Reduced configuration and maintenance costs through remote configuration
- Flexibility in adapting to customer protocols and applications

SATELLINE-3AS VHF

SATEL order code SATELLINE-3AS VHF SATELLINE-3ASd VHF SATELLINE-3AS VHF C SATELLINE-3ASd VHF C	YM5000 YM5010 (with display) YM5020 (with cooling part) YM5030 (with display and cooling part)
Frequency	135174 / 218238 MHz
Tuning range	135155, 138160,155174, 218238 MHz
Channel width	12.5 / 25 fixed kHz
RX sensitivity	-115 dBm
TX power (max.)	5 W
Interface	RS-232, -422, -485
Operating voltage	+9 +30 Vdc
Power consumption TX / RX	6.6 W @ 1 W, 22 W @ 5 W / 1.7 W
Data speed (max.) radio / serial	19200 bps / 38400 bps

SATEL launches a new product family SATEL-EASy+, which has an improved LCD display to enable easy configuration, an improved MCU capacity and variable physical interfaces available. It enables compatibility with SATELLINE-EASy and -M3-TR4 based radios as well as with SATELLINE-3AS NMS modems. The first product variant is for 400 MHz frequency band and with 1W output power. Other frequencies will follow the soonest, ask more from SATEL.

HW

- New generation mechanics
- Operating voltage +6...30 VDC
- Improved LCD display
- Improved MCU capacity
- Variable physical interfaces (D15, RJ45, USB, IO's)

FW

- NMS Protocol Compatibility (With routing, diagnostics and packet filters)
- ETH & TCP/IP Connectivity
- BT/BLE Connectivity
- DRM Feature support (IP networking, Cyber security)
- FW Over-The-Air Update *)

SW/DM

- Legacy support for SATEL NMS PC Software
- NETCO Stacks compatibility *) (Configuration + Monitoring)
- NETCO Mobile compatibility *)

RX sensitivity TX power (max.) Interface

SATEL-EASY+

SATEL order code

Frequency

Tuning range

Channel width

RS-232, -422, -485 (default) USB, ETH, BT (optional variant*)

TBD 400 MHz, 1W (without display)

TBD 400 MHz, 1W (with display)

12.5 / 20 / 25 kHz programmable

-116 dBm @ 12.5 kHz (4FSK) / -112 dBm @ 25 kHz (4FSK)

-106 dBm @ 25 kHz (16FSK)

403 - 473 MHz

70 MHz

+7 ... +27.5 VDC (+20 % / -15 %) Operating voltage

Power consumption TX / RX < 6.0 W / < 1.4 W

Data speed (max.) radio / serial 28800 bps / 115200 bps

THE FOLLOWING **SOFTWARE ARE SUPPORTED:**

- SaTerm (terminal SW for SL commands or data transmit/ reception)
- SATEL Configuration Manager (Configuration)
- NETCO Stacks *) (Configuration and monitoring)
- NETCO Mobile *) (Configuration over BT)
- SATEL NMS PC (Configuration and monitoring)

















^{*)} Ask availability from SATEL.

UHF & LICENCE FREE RADIO MODEMS

IP67 RADIO MODEMS



UHF RADIO MODEM

SATELLINE-EASy

YM6500 / YM6505 YM6510 / YM6515 (with AES) YM6550 / YM6555 (with display) YM6560 / YM6565 (with display and AES)
330 420 / 403 473 MHz
90 / 70 MHz
12.5 / 20 / 25 kHz programmable
-114 dBm
1 W
Port1: RS-232 fixed Port2: RS-232 / -422
+3 +9 / +6 +30 Vdc
7 W / 1.2 W
19200 bps / 38400 bps







YM6550/ YM6555 YM6560/ YM6565

LICENCE FREE RADIO MODEM

SATELLINE-EASy 869

OATELLINE LASY COS	
SATEL order code SATELLINE-EASy 869 SATELLINE-EASy 869	YM6501 YM6551 (with display)
Frequency	869.4125 869.6375 MHz (865 867 MHz for India)
Channel width	25 kHz
RX sensitivity	-111 dBm
TX power (max.)	500 mW (1 W for India)
Interface	RS-232, -422
Operating voltage	+6 +30 Vdc
Power consumption TX / RX	TX 3.8 W (869 MHz)/7 W (865 MHz)/ RX 1.2 W
Data speed (max.) radio / serial	19200 / 38400 bps





YM6501

YM6551

SOLUTIONS FOR THE TOUGHEST PLACES

SATEL Compact-4BT for heavy-duty outdoor use

SATEL Compact-4BT is an IP67 (NEMA 6) classified UHF radio modem with integrated battery, Bluetooth, wide tuning range and selectable channel spacing. It is designed for easy mobile use in demanding field conditions. IP67 ensures it is waterproof and secured against dust. SATEL Compact-4BT can be configured by using the well-known SATEL Configuration Manager or SaTerm programs, or by a mobile application called SATEL NETCO mobile. Mobile application can be downloaded from Google Play.



SATEL Compact-4BT

SATEL order code	YM6590 (YM6591 w/o AES)
Frequency	403473 MHz
Tuning range	70 MHz
Channel width	12.5 / 25 kHz (software selectable)
RX sensitivity	-116 dBm
TX power (max.)	1 W
Interface	RS-232 / USB
Operating voltage	+12 +30 Vdc
Power consumption	Charging: 7.4 W Charging + RX: 8.4 W Charging + TX: 13.2 W @ 1 W RF Device OFF: 0.46 W RX: 1.32 W TX: 5.8 W @ 1 W RF
Data speed (max.) radio / serial	28800 / 115200 bps

Ask the availability for 915 MHz version!

IP67 RADIO MODEMS

IP67 RADIO MODEMS



LICENCE FREE RADIO MODEM

SATEL Compact-Proof (869 MHz)					
SATEL order code	YM6575 with battery YM6576 w/o battery				
Frequency	869.4125 869.6375 MHz (865 867 MHz for India)				
Channel width	25 kHz				

RX sensitivity

TX power (max.) 500 mW (1 W for India)

Interface RS-232

Operating voltage +9...+16 Vdc

Power consumption TX / RX TX 3.8 W (869 MHz) / 7 W (865 MHz) / RX 1.2 W

Data speed (max.) radio / serial 19200 bps / 38400 bps

-111 dBm

IP67 RADIO MODEM

SATEL Compact-Proof	
SATEL order code	YM6570 / YM6573 (with battery) YM6571 / YM6574 (w/o battery)
Frequency	330420 / 403473 MHz
Tuning range	90 / 70 MHz
Channel width	12.5 / 20 / 25 kHz programmable
RX sensitivity	-114 dBm
TX power (max.)	1 W
Interface	RS-232
Operating voltage	+9 + 16 Vdc
Power consumption TX / RX When idle (no charging and modem off)	7 W / 1.2 W 6 mW
Data speed (max.) radio / serial	19200 bps / 38400 bps

BATTERY for SATEL Co	mpact-Proof	
Capacity and type	7.2 V, 8700 mAh, Li-Ion	
Charging current (max.)	1.6 A	
Charging time (empty to full)	5.5 h @ + 25 °C	
Charging voltage	+9 + 16 Vdc	
Max. time of operation	+60°C (1W) +60°C (50% TX / RX ratio 1W) -20°C (1W) -20°C (50% TX / RX ratio 1W) -20°C RX	13.8 h 22.2 h 10.5 h 16.9 h 44 h

SATELLINE-4Pro SATEL order code YM6804 406.180 ... 470 MHz Frequency Tuning range 63.8 MHz Channel width 12.5 / 25 kHz RX sensitivity <-117 dBm TX power (max.) 35 W Interface RS-232 Operating voltage +9 ... +16 Vdc 120 W / 1.8 W Power consumption TX / RX 28800 bps / 115200 bps Data speed (max.) radio / serial

SATELLINE-EASy Pro	
SATEL order code	YM6803
Frequency MHz	403 473 MHz
Tuning range	70 MHz
Channel width kHz	12.5 / 20 / 25 kHz programmable
RX sensitivity	-114 dBm
TX power (max.)	35 W (25 W as an order option)
Interface	RS-232
Operating voltage	+9 +16 Vdc (≥+12 Vdc @ 35 W)
Power consumption TX / RX	120 W / 1.8 W
Data speed (max.) radio / serial	19200 bps / 38400 bps



IP69K RADIO MODEMS

SATEL EASy-Proof	
SATEL order code	YM6580 / YM6480 YM6585 / YM6485 (with AES)
Frequency	330 420 / 403 473 MHz
Tuning range	90 / 70 MHz
Channel width	12.5 / 20 / 25 kHz programmable
RX sensitivity	-114 dBm
TX power (max.)	1 W
Interface	RS-232
Operating voltage	+6 +30 Vdc
Power consumption TX / RX	7 W / 1.2 W
Data speed (max.) radio / serial	19200 bps / 38400 bps
Note	Interface connector: Deutsch DT04-6P-CL09

SATEL Proof-TR4 / TR9 YM6583 SATEL Proof-TR4 with AES SATEL order code YM6584 SATEL Proof-TR4 w/o AES YM6587 SATEL Proof-TR9 403 ... 473 / 902 ... 928 MHz Frequency Channel width 12.5 / 20 / 25 kHz @ TR4 Spreading method Frequency hopping @ TR9 RX sensitivity -118 ... -105 dBm TX power (max.) 1 W RS-232 (TD, RD lines) Interface +6 ... + 30 Vdc Operating voltage Power consumption TX / RX TX max. 4 ... 7 W / RX < 1 W 28800 bps / 115200 bps @ TR4 Data speed (max.) radio / serial 115200 bps / 115200 bps @ TR9

SATEL has a wide range of OEM radio modules for system manufacturers to integrate into customer solutions. They are secure, customizable and flexible in mounting options. SATEL's solutions are widely compatible and also support other manufacturers' radio protocols.

The latest addition to SATEL radio modules is the SATEL GO radio module family. SATEL GO modules introduce new revolutionary features: two frequencies in the same small module and more practical interfaces. The design is compact and the integration easy.

The first products available in SATEL GO product family are dual-band and multimode transceivers for the licensed 410-475 MHz and license-free 902-928 MHz bands. Those are compatible with SATELLINE product line on 410-475 MHz and Freewave and Intuicom products on 902-928 MHz.

SATEL-TR49 SnapOn


SATEL-TR49 SnapOn fits to a standard PCIe bus. This ma compatible with millions of equipment already in the ma and the integration is easy. If there is Mini PCIe bus, it car other technologies such as cellular and LoRa. Ideal for re-IoT applications!

- Ultra-compact design
- Easy integration and deployment
- Possibility of power over USB (max 500 mW, more with extra input)
- Robust mounting and interfaces

kes it arket, n replace eal-time	
og Č	

SATEL order code	TBD
Frequency	410 475 / 902 928 MHz
Channel width	12.5 / 25 kHz @ 400 MHz
Spreading method	Frequency hopping @ 900 MHz
RX sensitivity	-120 dBm @ 400 MHz -109 dBm @ 900 MHz
TX power (max.)	1 W
Interface	CMOS / UART
Operating voltage	+3.3 Vdc +/-9%
Power consumption TX / RX	4.5 – 4.8 W / 400 mW @ 400 MHz 4.0 W / 400 mW @ 900 MHz
Data speed (max.) radio / serial	19200 bps (115200 bps @ 900 MHz) / 115200 bps

SATEL-TR49	
SATEL order code	YM8490 region all, with AES YM8495 region all, without AES YM8500 region US/CA, with AES YM8505 region US/CA, without AES YM8510 region Australia, with AES YM8515 region Australia, without AES YM8520 region New-Zealand, with AES YM8525 region New-Zealand, without AES
Frequency	410 475 / 902 928 MHz
Channel width	12.5 / 20 / 25 kHz @ 400 MHz
Spreading method	Frequency hopping @ 900 MHz
RX sensitivity	-120 dBm @ 400 MHz -109 dBm @ 900 MHz
TX power (max.)	1 W
Interface	CMOS / UART
Operating voltage	+3.7 +5.5 Vdc
Power consumption TX / RX	4.8 W (TX 1 W) / 440 mW (RX) @ 400 MHZ 4.1 W (TX 1 W) / 440 mW (RX) @ 900 MHz
Data speed (max.) radio / serial	19200 bps (115200 bps @ 900 MHz) / 115200 bps




SATELLINE-M3-TR4 **SATELLINE-M3-TR9** YM7400, YM7410 w/o AES, SATEL order code YM7405 w/o AES DTE connector on TOP SATEL order code Frequency 403 ... 473 MHz Tuning range 70 MHz Frequency 12.5 / 20 / 25 kHz programmable Channel width Spreading method RX sensitivity / TX power (max) -116 dBm / 1 W RX sensitivity / TX power (max.) CMOS-UART Interface Interface +4 Vdc Operating voltage Operating voltage Power consumption TX / RX 4.7 W / 0.73 W Power consumption TX / RX



Data speed (max.) radio / serial

TRANSCEIVER WITH 16FSK MODULATION

28800 bps / 115200 bps



Data speed (max.) radio / serial

SATELLINE-M3-TR3

RX sensitivity / TX power (max.)

Power consumption TX / RX

Data speed (max.) radio / serial

SATEL order code

Tuning range Channel width

Operating voltage

FREQUENCY HOPPING TRANSCEIVER MODULE

YM7000, YM7100 w/o AES

12.5 / 25 kHz programmable

403 ... 473 MHz

-116 dBm / 1 W

CMOS-UART

4.7 W / 0.73 W

19200 bps / 115200 bps

+4 Vdc

70 MHz

YM7900 region all

YM7915 region AU

Frequency hopping

902 ... 928 MHz

-109 dBm / 1 W

+3.5 ... +5.5 Vdc

CMOS-UART

3.2 W / 0.3 W

115200 bps

YM7910 region US/CA

YM7905 DTE TOP/U.FL same side

SAT	ELLI	NE-I	M3-'	TR8	

SATEL order code	YM7800, YM7810 w/o AES	SATEL orde
Frequency	868 870 MHz (865 867 MHz for India)	Frequency
Tuning range	2 MHz	Tuning rang
Channel width	25 kHz	Channel wi
RX sensitivity / TX power (max.)	-112 dBm / 0.5 W (1 W for India)	RX sensitivi
Interface	CMOS-UART	Interface
Operating voltage	+4 Vdc	Operating v
Power consumption TX / RX/	TX 4.3 W (869 MHz) / 7.3 W (865 MHz) / RX 0.875 W	Power cons
Data speed (max.) radio / serial	19200 bps / 115200 bps	Data speed



LICENCE FREE



TRANSCEIVER

SATELLINE-M3-R4

SATEL order code	YM7050, YM7150 w/o AES, YM7250 w/o AES DTE connector on TOP
Frequency	403 473 MHz
Tuning range	70 MHz
Channel width	12.5 / 25 kHz
RX sensitivity	-116 dBm
Interface	CMOS-UART
Operating voltage	+4 Vdc
Power consumption RX	0.73 W
Data speed (max.) radio / serial	28800 bps / 115200 bps



RECEIVER WITH 16FSK MODULATION

SATELLINE-M3-R3

SATEL order code	YM6900
Frequency	403 473 MHz
Tuning range	70 MHz
Channel width	12.5 / 25 kHz programmable
RX sensitivity	-114 dBm
Interface	CMOS-UART
Operating voltage	+4 Vdc
Power consumption RX	0.5 W
Data speed (max.) radio / serial	19200 bps / 115200 bps



RECEIVER

CUSTOMIZED RADIO MODEMS

SATELLINE-M3 VHF	
SATEL order code	YM6000
Frequency	135174 / 218238 MHz
Tuning range	135155, 138160, 155174, 218238 MHz
Channel width	12.5 / 25 fixed kHz
RX sensitivity / TX power (max.)	-115 dBm / 1 W
Interface	RS-232, -422, -485
Operating voltage	+9 +30 Vdc
Power consumption TX / RX	6.6 W / 1.7 W
Data speed (max.) radio / serial	19200 / 38400 bps

Examples of the customized radio modems.
Ask your local SATEL distributor about the various options.



SATELLINE-M3-TR1

SATEL order code	YM6300 / YM6305 YM6310 / YM6315 (with AES)
Frequency	330 420 / 403473 MHz
Tuning range	90 / 70 MHz
Channel width	12.5 / 20 / 25 kHz programmable
RX sensitivity / TX power (max.)	-114 dBm / 1 W
Interface	RS-232, -422, LVTTL, TTL
Operating voltage	+3 +9 / +6 +30 Vdc
Power consumption TX / RX	3 W @ 0.5 W, 7 W@ 1 W / 1.2 W
Data speed (max.) radio / serial	19200 / 38400 bps



SATELLINE-M3-TR1 869

SATEL order code	YM6301
Frequency	869.4125 869.6375 MHz (865 867 MHz for India)
Tuning range	0.25 MHz (2 MHz India)
Channel width	25 fixed kHz
RX sensitivity / TX power (max.)	-111 dBm/ 0.5 W (1 W for India)
Interface	RS-232, -422, LVTTL, TTL
Operating voltage	+6 +30 Vdc
Power consumption TX / RX	3.8 W / 1.2 W
Data speed (max.) radio /serial	19200 bps / 38400 bps



SATELLINK I/O CONVERTERS









SATEL I-LINK 300

* Extension module for I-LINK

SATEL i-LINK

SATEL I-LINK 100

SATEL I-LINK 200

	SATEL order code	Digital I/Os	Analog I/Os 4-20 mA	Pulse counter	Connectors, switches
SATEL i-LINK	Y10090	2	-	•	Screw conn. / 16-pin 2x8 f / DIP
SATEL I-LINK 100	YI0007	4	2	-	Screw conn. / D15m / D15f / DIP
SATEL I-LINK 100 MB	YI0017	4	2	-	Screw conn. / D15m / D15f / DIP
SATEL I-LINK 200*	YI0009	4	2	-	Screw conn. / D15m / D15f / DIP.
SATEL I-LINK 300*	YI0010	6	-	-	Screw conn. / D15m / D15f / DIP

SATEL-LP MODULES



			L-				
•	/ A \	_	_			~	74 L
	/ - \	_	_	_	_	~	

SATEL order code	YM0424
Frequency	2.4002 2.4785 GHz
Tuning range	FHSS
RX sensitivity / TX power (max.)	-106 dBm / 100 mW
Interface	T-BUS (for extension modules), RS-232, -485
Operating voltage	+19.2 +30.5 Vdc
Power consumption (Max. @ 24 Vdc)	≤ 65 mA
Dataspeed (max.)	250 kbps



SATEL-LP9

SATEL order code	YM0409
Frequency	902 928 MHz
Tuning range	FHSS
RX sensitivity / TX power (max.)	-112 dBm / 1000 mW
Interface	T-BUS (for extension modules), RS-232, -485
Operating voltage	+10.8 +30.5 Vdc
Power consumption (Max. @ 24 Vdc)	328 mA
Dataspeed (max.)	500 kbps



SATEL-LP8

UNITE EI U	
SATEL order code	YM0408
Frequency	869.4 869.65 MHz
Tuning range	FHSS*
RX sensitivity / TX power (max.)	-122 dBm / 500 mW
Interface	T-BUS (for extension modules), RS-232, -485
Operating voltage	+19.2 +30.5 Vdc
Power consumption (Max. @ 24 Vdc)	≤ 65 mA
Dataspeed (max.)	120 kbps





SATEL-LP I/O EXTENSION MODULES

SAIEL-LP I/C	EVIENDIO	N MODULES
Product	SATEL order code	Interfaces
SATEL-LP-DI4	YI0101	4 x digital inputs (0 250 V AC/DC)
SATEL-LP-DOR4	YI0102	4 x digital relay outputs (6 A, 24 Vdc / 250 Vac)
SATEL-LP-AI4	YI0103	4 x analog inputs (020 mA / 4 20 mA)
SATEL-LP-AO4	YI0104	4 x analog outputs (0 20 mA / 4 20 mA, 0 10 Vdc)
SATEL-LP-DAIO6	YI0105	1 x analog inputs (0 20 mA / 4 20 mA) 1 x analog outputs (0 20 mA / 4 20 mA, 0 10 Vdc) 2 x digital inputs / outputs (0 250 V AC/DC)
SATEL-LP-DI8	YI0106	8 x digital inputs (0 30.5 Vdc) OR 2 x pulse inputs (0 100 Hz)
SATEL-LP-DO8	YI0107	8 x digital transistor outputs (30.5 Vdc / 200 mA)
SATEL-LP-PT100	YI0108	4 x PT 100 resistance thermometer inputs (-50 °C \dots +250 °C)



20 21



NETCO

NETCO is a intuitive and user friendly network configuration program for SATEL XPRS IP radio router. It is designed to make configuration as easy as possible. With NETCO a fully functional communication network can be configured with a few simple clicks. It has SATEL XPRS IP radio router -based network comissioning and it can configurate large network (up to 5000 devices) without delays.




Configuration Manager

SATEL Configuration Manager (CM) is available for SATEL-LINE-M3-TR1, -EASy, -EASy Pro, -M3-R3, -M3-TR3, -M3-TR4, -M3-TR8, -EASy 869, -M3-TR1 869, SATEL Compact-4BT, Compact-Proof, EASy-Proof, TR49 and TR49 SnapOn. The program makes it possible to edit the modem settings and update the firmware.



Network Management System software for creating and managing SATELLINE-3AS VHF, SATEL-EASy+ and SATEL XPRS IP radio networks, including the graphical design of topology and message routing or repeater functions, remote modification of settings, and logging and trending of field data.





SaTerm

SaTerm is software, which can be used for configuration, testing, reprogramming and for updating the firmware of the SATELLINE-EASy and -Easy Pro modems.



SATELLINK PC Pro

Point-to-multipoint program for driving SATEL I-LINK and i-LINK I/O-converters. Operate systems, which are connected to the I/O-ports, change values, collect pulses and monitor the radio link. For max. 127 slaves.



FCS Monitor

Free Channel Scanning Monitor program can be used for setting the FCS parameters and for loading them to modems and for monitoring the channels for noise or interference.

Channel List Editor

Channel List Editor program can be used for creating the channel list for Epic Promodems.

Help Editor

Help Editor can be used for creating and editing different language versions for Configuration Manager.

Antennas & cables

Antennas

- Half Wave Antennas for frequencies 400 ... 470 MHz for short distances
- Quarter Wave Antennas for frequencies 400 ... 470 MHz and 869 MHz for short distances
- Helix Antennas for frequencies 400 ... 470 MHz for short distances
- Directional Antennas for frequencies 330 ... 470 MHz, 869 MHz and 135 ... 174 / 218 ... 238 MHz for long distances
- Omnidirectional Antennas for frequencies 330 ... 470 MHz, 869 MHz and 135 ... 174 / 218 ... 238 MHz for long distances.


Cables

- CRF-1 RG58 lenght 1 meter with TNC male / TNC female -connectors
- CRF-5F RG58 lenght 5 meter with TNC male / TNC female -connectors or CRF-5M TNC male / TNC male -connectors
- ECOFLEX10 low loss (0.9 dB / 10 m) cable for cable lengths over 20 meter with N or TNC -connectors.
- ECOFLEX15 low loss (0.6 dB / 10 m) cable for cable lengths over 20 meter with N -connectors.

We can also offer a wide range of interface and power cables, for example:

- CRS-2M length 2 meter, includes power supply wires, with D15 / D9 male or CRS-2F female -connectors
- CRS-PB length 2 meter, includes power supply wires, with D15 / D9 male -connectors for RS-485 interface
- CRS-35W 8-pin 2 m cable ODU 8-pin male / D9 female
- C-P-35W 2m Power cable 2 m, ODU 4-pin male / 4 mm lab plugs
- DC / RS232 Cable 1 m, M12 / D9 female / 2.1 mm DC jack male

Please contact your local distributor to get more information regarding cable types.





SATEL XPRS Multigateway is a secure edge computing platform, combining multiple technologies in one device. It offers connectivity options for redundant back haul over LTE or SATEL XPRS IP radio, while SATEL GO modules communicate in local network, for example with SATELLINE-EASy modems. Various low-power radios are supported as well, so the local sensor connectivity could be with LoRa or Bluetooth. In addition to using SATEL XPRS IP radio as a back haul connection, the Multigateway can operate as a secure, high-available master device for IP radio network, where the slave devices are SATEL XPRS or SATEL XPRS Optimum IP radio routers.

Customized, user specific software can be embedded to Multigateway, enabling for example data analysis and local storage or customer specific interfaces towards cloud services.

SATEL XPRS Multigateway use cases are for example concentrator communications for Automated Meter Infrastructure, NTRIP Bridge for precision positioning applications, master device for Smart Grid communications or connectivity for water treatment application. Even better, the SATEL XPRS Multigateway may have multiple roles simultaneously, as each application may have their own communication module in one device.

SATEL XPRS Multigateway enables savings by reducing complexity and footprint of the network. It also provides significant reliability upgrade. The enhanced security and high-availability features help avoid communication failures and downtime, and thus help avoid high costs in mission-critical applications.

EXAMPLES OF INTEGRATED CONNECTIVITY:

- Wifi
- Bluetooth
- SATEL XPRS IP radio (QAM modulation)
- SATEL GO modules /
- SATELLINE-EASy family modems
- 2G/3G/4G (5G in the future)
- LoRa




Selection guide

		∟ comp	atible	_					- compa	atible –												1	
1) LP24 2) LP8	SATEL XPRS radio router						0	Joe		_		84	SATELLINE-M3-TR3, TR4		n *)	SATEL Proof-TR4, TR9 *)	·		<u>ه</u>	869			
3) LP9	0.0	¥	生				'Pn	Ä	of	.4B	.E	3,1	R3,		od	*,	E		98/	.R	88		
4) SATEL XPRS IP	adi	4S.	3 <	AS		Pro	AS	ಕ್ಷ	o o	ಕ್ಷ	3-1	3-5	3-T	_	na	%	3-1		AS	3-⊤	3-1		
radio router	Sr	3,	Σ	l ä	×	4-	E E	l ğ	, -Ž	μ	Σ	Σ	Σ	* 61	61	9	=		2	Σ	Σ	ž	
5) Check product details	AP.	<u>=</u>	=	<u>Z</u>	Ë	Z	<u>=</u>	<u>ō</u>	EA	Ō	<u>=</u>	Z	<u>=</u>	ΤŘ	Ţ.	P. C	=		Ξ	Z	<u>=</u>	∃	
3) check product details	Ī	SATELLINE-3AS VHF	SATELLINE-M3 VHF	SATELLINE-EASy	SATEL-EASy+	SATELLINE-4Pro	SATELLINE-EASy Pro	SATEL Compact-Proof	SATEL EASy-Proof	SATEL Compact-4BT	SATELLINE-M3-TR1	SATELLINE-M3-R3, R4	🗒	SATEL-TR49 *)	SATEL-TR49 SnapOn *)	핕	SATELLINE-M3-TR9 *)		SATELLINE-EASy 869	SATELLINE-M3-TR1 869	SATELLINE-M3-TR8	SATEL I-LINK	SATEL-LP
	SA	SA	SAS	SA	SA	SA	SA	SAS	SAS	SA	SAS	SAS	SA	SA	SA	SAS	S		SAS	SA	SAS	SAS	S
Frequency range UHF																							
VHF																							
UHF & Licence free																				•			
Interfaces																		I					
RS-232	•	•	•	•	•	•	•	•	•	•	•					•			•	•		•	
RS-422	٠	٠	•								•								•	٠			
RS-485	•	•	•		•																		•
TTL / LV-TTL CMOS-UART											•								•	٠			
Ethernet	4)											•	•	•	•		١.				•		
USB	4)																						
Digital / Analog I/O	-,																						
Pulse counter																							
Bluetooth										•													
Tuning range																							
0.25 MHz																			•	٠	•		
4 MHz 20 MHz		5)	5)				•																
45 MHz		3)	3)			5)																	
65 MHZ						3)																	
70 / 90 MHz					5)			5)		5)													
FHSS																							
Channel width kHz																							
Fixed (12.5 or 20 or 25)			•																5)	5)			
Programmable (12.5 / 20 / 25)				•	•		•	•	•		•	•				•							
Programmable (12.5 / 25) Programmable (12.5 / 25) (4)150)						•				•			٠	٠	٠								
Programmable (12.5 / 25) (*/150) FHSS	•																١.						
Max. TX power																-		+					
100 mW																		Т					1)
500 mW																				•	•		2)
1 W									•	•			•	٠	•								3)
5 W	•	•																					
10 W																							
35 W Operating voltage range						•	•										+	+	-				
+ 4 Vdc																							
+3 +9 Vdc																							
+3.7 +5.5 Vdc														•									
+3.3 Vdc +/- 9%															•								
+6 +30 Vdc				•					•		•					•			•	•			
+9 +16 Vdc						•	٠	•															
+9 +30 Vdc +10.6 +30 Vdc		•	•																				
+10.830.5 Vdc																							3)
+11.8 +30 Vdc																		Т					-,
+12 +30 Vdc																							
+19.2+30.5 Vdc																							1), 2
Battery								•		٠								4					
Housing																							
Plastic IP20 Aluminium IP44																							
Aluminium IP52		·			•														•				
Aluminium IP67																							
Aluminium IP69K																							
Plastic / Aluminium IP67										•													
Sheet metal aluminium / Stainless steel			•								•									•		•	
Module: PCB card only											•	٠	٠	٠	٠		٠.	+	_	٠	•		
Interface connector RJ-45	4)				E/																		
RJ-45 D9	4)				5)																		3)
					5)																		3)
D15					"																		
D15 ODU 8 pin																							
					I =\										•								
ODU 8 pin 26 pin header / 26 pin strip USB					5)				1			•	•	•					- 1				
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket					5)																		
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09					5)				•							•							
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector					5)				•							•							
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector M12 circular					5)				•	•						•							
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector					5)				•							•							
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector M12 circular COMPATIBILITY					•	•	•	•	•		•	•			•						•		
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector M12 circular COMPATIBILITY Software								•			•	•	•	•	•					•		•	
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector M12 circular COMPATIBILITY Software Configuration Manager		•										•	•	•	•							•	
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector M12 circular COMPATIBILITY Software COMPATIBILITY SATELLINK PC Pro SATELLINK PC Pro SATERM NMS PC	•	•			•	•	•	•	•		•	•	•	•	•					•		•	
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector M12 circular COMPATIBILITY Software Configuration Manager SATELLINK PC Pro SaTERM NMS PC FCS				•	•	•	•	•			•	•		•	•					•			
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector M12 circular COMPATIBILITY Software Configuration Manager SATELLINK PC Pro SaTerm NMS PC FCS NETCO Mobile						•	•	•	•		•	•	·		•					•		•	
ODU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector M12 circular COMPATIBILITY Software Configuration Manager SATELLINK PC Pro SaTERM NMS PC FCS					•	•	•	•	•		•	•	·	·	•					•		•	
DDU 8 pin 26 pin header / 26 pin strip USB 1.27 mm pitch socket Deutsch DT04-6P-CL09 Screw connector M12 circular COMPATIBILITY Software Configuration Manager SATELLINK PC Pro SaTerm NMS PC FCS NETCO Mobile LP-CONF					•	•	•	•	•		•	·	•	•	•					•		•	

Check the product details for frequency compatibili

Available frequencies for SATEL radio modems



Channel width and data speed

		Max. serial data speed			
Channel width	12.5 kHz	·			
SATEL XPRS IP radio router	19.2 kbps (FSK) 60.5 kbps (QAM)		38.4 kbps (FSK) 121 kbps (QAM)	230.4 kbps (FSK)	256 kbps
SATELLINE-EASy Pro SATELLINE-EASy SATEL EASy-Proof SATEL Compact-Proof	9600 bps 9600 bps 9600 bps 9600 bps	9600 bps 9600 bps 9600 bps 9600 bps	19200 bps 19200 bps 19200 bps 19200 bps		38400 bps 38400 bps 38400 bps 38400 bps
SATEL-EASy+ SATEL Compact-4BT	14400 bps 14400 bps	14400 bps 14400 bps	28800 bps 28800 bps		115200 bps 115200 bps
SATELLINE-3AS VHF	9600 bps		19200 bps		38400 bps
SATEL Compact-Proof 869 SATELLINE-EASy 869			19200 bps 19200 bps		38400 bps 38400 bps

Channel width	FHSS
SATEL LP-8	max. air data speed 120 kbps
SATEL LP-24	max. air data speed 250 kbps
SATEL LP-9	max. air data speed 500 kbps



Protocols

SATEL radio modems are compatible with all commonly used industrial protocols. Here are some examples of the protocols: ANSI, ASCII, CACTUS, COMLI, DNP 3.0 Serial & IP, 4 Exoline, HostLink, IEC 60870-101, IEC 60870-104, IEC 61850, Mewtocol, Modbus ASCII, Modbus RTU, Modbus TCP, Profibus DP, R-com, RP-570, RP-571, SATELLINK, S-bus, Siemens 3946 (R), SNMP, TCP/IP, SATEL NMS, Rockwell DF etc.

Ask for more information from your local distributor.

Disclaimer

©2019 SATEL Oy. All rights to this catalogue are owned solely by SATEL Oy. (referred to in this catalogue as SATEL). All rights reserved. The copying of this catalogue (without the written permission from the owner) by printing, copying, recording or by any other means, or the full or partial translation of the manual to any other language, including all programming languages, using any electrical, mechanical, magnetic, optical, manual or other methods or devices is forbidden. SATEL reserves the right to change the technical specifications or functions of its products, or to discontinue the manufacture of any of its products or to discontinue the support of any of its products, without any written announcement and urges its customers to ensure, that the information at their disposal is valid. SATEL software and programs are delivered "as is". The manufacturer does not grant any kind of warranty including guarantees on suitability and applicability to a certain application. Under no circumstances is the manufacturer or the developer of a program responsible for any possible damages caused by the use of a program. The names of the programs as well as all copyrights relating to the programs are the sole property of SATEL. Any transfer, licensing to a third party, leasing, renting, transportation, copying, editing, translating, modifying into another programming language or reverse engineering for any intent is forbidden without the written consent of SATEL.

IMPORTANT

SATEL PRODUCTS HAVE NOT BEEN DESIGNED, INTENDED NOR INSPECTED TO BE USED IN ANY LIFE SUPPORT RELATED DEVICE OR SYSTEM AND ARE GRANTED NO FUNCTIONAL WARRANTY IF THEY ARE USED IN ANY OF THESE APPLICATIONS.

Distributors L

AUSTRALIA

ROJONE PTY LIMITED +61 2 9829 1555 warren@rojone.com.au www.rojone.com.au

Rojone is serving Australia and New Zealand

AUSTRIA See Germany

BELGIUM See The Netherlands

BOSNIA AND HERZEGOVINA

See Croatia

SATELRADIO COMUNICAÇÃO

+55 11 3090 4094 hotelho@satelradio.com.br

www.satelradio.com.br

IDEAL BRASIL +55 15 99106 3505

iaimilton oliveira@idealbrasil.com.bi www.idealbrasil.com.br

CAMBODIA See South East Asia

CANADA

MDA CONTROLS INC.

+1 905 845 3666 orit.altman@mdacontrols.com

CHILE

METCOM LIMITADA

+56 2 2335 3812 gailrybertt@metcomchile.cl www.metcomchile.cl

CHINA P.P. SATEL CHINA CO., LTD +86 20 8251 4925

info@satel.cn

CROATIA ADRINET D.O.O.

+358 1 8886 884 adrinet@adrinet.hr www.adrinet.hr

CZECH REPUBLIC

CONTROLTECH S.R.O. +420 321 7420 11 info@controltech.cz www.controltech.cz

ControlTech s.r.o. is serving Czech Republic and Slovak Republic

DENMARK

COMSYSTEM A/S +45 49 139 693

salg@comsystem.dk

I.C.E.E.S

+20 2 2267 0427 info@icees-eg.com www.icees-eg.com

ESTONIA

ALARMTEC AS +372 6 511 500

alarmtec@alarmtec.ee www.alarmtec.ee

Alarmtec AS is serving Estonia, Latvia and Lithuania.

FRANCE COMATIS

+33 1 3930 2900 info02@comatis.com

www.comatis-radiomodems.com COMATIS is serving France and Northern Africa countries excluding Egypt

GERMANY

WELOTEC GMBH

+49 2554 9130 00 info@welotec.com

Welotec is serving Germany and Austria

GREECE INTELLIGENT AUTOMATION

CONTROL SYSTEM SA +302 310 515 495

HUNGARY CONTROLTECH S.R.O.

www.iacs.gr

+36 23 445 900 info@controltechhungary.hu www.controltechhungary.h

ICELAND NAUST MARINE HF

+354 414 8080 haraldur@naust.is

www.naust.is

INDIA

LOTUS WIRELESS

+91 891 276 1678 www.lotuswireless.com

INDONESIA PT. INZAN PERMATA

IRFI AND

+62 21 875 2727

sales@inzanpermata.com www.inzanpermata.co.id

SIGMA WIRELESS **COMMUNICATIONS LTD**

pkinna@sigma.ie www.sigmawireless.com

Sigma Wireless Communications Ltd is serving Ireland and Northern Ireland

ISRAEL ARROWMID GROUP LTD

+972 36 247 080 info@arrowmid.com www.arrowmid.com

ITAIV SARTELCO SISTEMI S.R.L.

+39 039 629 051 sistemi@sartelco.it www.sartelco.com

ΚΔ7ΔΚΗ STΔΝ **AUTOMATION AND**

TECHNOLOGIES-SERVICE LTD

+7 727 277 4949

info@automation-trade.com www.automation-trade.com

KOREA THOMAS TRADING CO., LTD. +82 31 467 8554

system@thomas.co.kr www.thomas.co.kr

LATIN AMERICA-CARIBBEAN **SOLARES FLORIDA CORP**

Tel +1-305-592 0593 isolares@solaresflorida.com www.solaresflorida.com Solares Florida is serving part of the Latin America and Caribbean coul

LAOS See South East Asia

LATVIA, LITHUANIA

LUXEMBOURG

MALAYSIA DIGISELECT (M) SDN BHD

+6 03 5614 3167 enquirv@dgselect.com www.dgselect.com

MEXICO ROSSBACH DE MÉXICO, S.A. DE C.V.

+52 1 555 147 0547

ventas@rossbach.com.mx www.rossbach.mx

MIDDLE EAST

EASY WORLD AUTOMATION LLC +971 4 447 1137 sales@eworldme.com www.eworldme.com/en

SAUDI TELECOMMUNICATION

+966 13 820 0477 mansour@stpest.com www.stpest.com Saudi Telecommunication & Power is serving Saudi Arabia, Kuwait, UAE, Bahrain,

Qatar and Oman. **MONTENEGRO**

See Slovenia

THE NETHERLANDS SATEL BENELUX B.V.

+31 255 820 009 info@satelbv.nl www.satelbv.nl SATEL Benelux is serving The Netherlands, Belgium and Luxembourg

NEW ZEALAND

See Australia

NORTHERN AFRICA See France

NORWAY SATEL NORGE AS

+47 69 27 70 40 produktinfo@satel.no www.satel.no

MOR SRL

+51 1 222 6185 info@morslr.com www.morsrl.com

PHILIPPINES See South East Asia

POI AND

ASTOR MISSION CRITICAL SP. Z O.O. +48 60 178 3744

satel@astor.com.p www.astor.com.pl

PORTUGAL See Spain

RUSSIA **SATEL-RUSSIA**

+7 495 760 1772 A Samokhin@satel-russia.com www.satel-russia.com

SERBIA See Slovenia

SINGAPORE

See South East Asia

SLOVAK REPUBLIK See Czech Republic

SLOVENIA

METRONIK D.O.O +386 1 514 0800 info@metronik.si www.metronik.si METRONIK d.o.o is serving Slovenia

Serbia and Montenegro

SOUTH AFRICA **INTEGR8 & AUTOM8** +27 82 456 0902 mark@satel.co.za www.i8a8.co.za Integr8 & Autom8 serves Africa.

excluding Northern Africa and Egypt.

CSTREAM

+27 12 664 4515 info-cs@cstream.co.za www.cstream.co.za

SPAIN

SATEL IBERIA +34 91 636 22 81

info@satel-iberia.com www.satel-iberia.com

SATEL IBERIA is serving Spain and Portugal.

SWEDEN

INDUO AB +46 8 659 43 00 info@induo.com www.induo.com

SWITZERLAND

SATEL SWITZERLAND TUNCELLI CCS +41 21 729 59 83 ctuncelli@satelch.com

www.satelch.com

SOUTH EAST ASIA SATEL OY IN S.E.A.

+66 899 276 966 janne.kankaanpaa@satel.com www.satel.com

SATEL Sales Manager Mr. Janne Kankaanpaa serves S.E.A. region (Philippines, Singapore, Kambodzha, Laos, plus other

TAIWAN ENVIRONMENTAL

SCIENCE & ENG'N CORP. +886 2 2963 4300 sales@esne.com.tw

www.esne.com.tw **THAILAND**

ENOVA INTEGRATION CO LTD

+662 961 0799 noppachai@enovagroup.net www.enovagroup.net

TURKEY **BILKO AS**

hilko@hilko-automation.com www.bilko-automation.com

UKRAINE CJSC NEW TECHNOLOGIES

+8 044 499 77 15 satel@ntech.kiev.ua www.ntech.kiev.ua

UNITED KINGDOM

+90 212 320 1383

SADERET LTD +44 1624 880366 andy@saderet.co.uk

XL SYSTEMS LTD

+44 1883 622 778 sales@xls.co.uk

UNITED STATES

SATEL U.S.A. +1 408 973 1740 info@satelusa.com

www.satelusa.com **ONYX NETWORKS TEXAS LLC**

+1 832 924 0125 sergio.martinez@onyxnetworks.us

URUGUAY

AEROMARINE S.A. +598 2 916 6456

mjn@aeromarine.com.uy www.aeromarine.com.uy

VIETNAM TRIEUHA TELECOMMUNICATIONS

+84 4 3572 0699 tuanav@gmail.com

Contact us SATEL

SATEL, Meriniitynkatu 17 P.O.Box 142, FI-24101 Salo FINLAND Tel. +358 2 777 7800 Fax +358 2 777 7810 info@satel.com

